


## Specifications

	<b>1214X</b>	<b>1221X</b>
<b>Type</b>	Electronic Printing / Display Calculator	Electronic Printing / Display Calculator
<b>Capability</b>	12 digits	12 digits
<b>Display</b>	12 digit Liquid Crystal Display	12 digit Liquid Crystal Display
<b>Printing</b>	Epson M32TL printer head	Epson M32TL printer head
<b>Printout color</b>	Blue/Red, two-color ribbon (negative results are printed in red)	Blue/Red, two-color ribbon (negative results are printed in red)
<b>Ink roll</b>	IR40T	IR40T
<b>Printing speed</b>	2.4 lines/second	2.4 lines/second
<b>Paper roll</b>	Width 57mm (2-11/16")/ Inner diameter 12mm (1/2")/ Outer diameter 50mm (2")	Width 57mm (2-11/16")/ Inner diameter 12mm (1/2")/ Outer diameter 50mm (2")
<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
<b>Power source</b>	Adaptor / 4 batteries (AA/1.5V/UM-3)	AC 220-240V 50/60 Hz
<b>Power consumption</b>	7 W	14 W
<b>Dimensions (WxLxH)</b>	152 x 217.5 x 16 to 55mm	212 x 278 x 18 to 64mm
<b>Weight</b>	445g	800g
<b>Adaptor (optional)</b>	Class 2 power adaptor unit rated: Input 230V~50Hz 7W, Output 6VDC  300mA 1.8VA	n/a