

# DYMO®

## LabelManager™ 360D



### CREATE LABELS FAST WITH SMART KEYS

Easy to create professional labels in and around the office. Type, format and print with one-touch Smart Keys.

#### Features

- Easy-to-use wide-format keyboard
- One-touch Smart Keys for fast formatting
- Save up to 9 frequently used labels
- Long lasting rechargeable battery pack
- 20+ ways to format text
- 200+ symbols and clip-art images
- Print up to 3/4 in (19 mm) wide labels



### Single Unit Includes:

- LabelManager 360D
- D1 Starter Label Cassette, 12mm x 3m Black on White
- Rechargeable Lithium-Ion Battery
- Quick Start Guide
- Charging Adapter
- 2 + 1 - Year Limited Warranty\*



| Quick Specs                 |                         |
|-----------------------------|-------------------------|
| Unit Dimensions (H x W x L) | 197 x 150 x 71 mm       |
| Weight (excluding battery)  | 610 g                   |
| Mac®/PC Compatible          | No                      |
| Accepts Label Sizes         | 6mm, 9mm, 12mm and 19mm |
| Tape Platform               | D1, Durables            |
| Resolution                  | 180 dpi                 |
| Printing System             | Thermal Transfer        |
| Print Speed                 | 12 mm/sec               |
| Barcodes                    | No                      |
| Cutter Type                 | Manual                  |
| Batteries                   | Rechargeable            |
| Adapter                     | Yes (included)          |
| Networking                  | No                      |
| Country of Origin           | China                   |

| Item Number                                       | Description                 |      | Length (cm) | Width (cm) | Height (cm) | QTY | EAN           | Customer Price |
|---|-----------------------------|------|-------------|------------|-------------|-----|---------------|----------------|
| 6868091   | LabelManager 360D QWERTY UK | Unit | 29.0        | 18.7       | 19.2        | 1   | 3501170879498 |                |
| <b>Accessories (www.dymo.com)</b>                 |                             |      |             |            |             |     |               |                |
| Contact your RS Components team for availability. | Charging Adapter            | Unit | 9.0         | 4.8        | 8.2         | 1   | -             |                |

\* +1 year if registered on the DYMO® website

## D1 Standard Polyester Labels

For hundreds of tasks around the office or home office, such as filing, storage and asset tracking.  
 Temperature rating: -18°C to 90°C

| D1 STANDARD LABELS (3 m)     | 6 mm  | 9 mm    | 12 mm   | 19 mm   |
|------------------------------|---|---------|---------|---|
| ABC                          | Contact your RS Components team for availability. |         |         |   |
| ABC                          | Contact your RS Components team for availability. |         |         |   |
| D1 STANDARD LABELS (7 m)     | 6 mm  | 9 mm    | 12 mm   | 19 mm   |
| ABC                          | 2086668   | 2030457 | 497432  | 2233038   |
| ABC                          | 2086630   | 2030441 | 497410  | 2233000   |
| ABC                          | 2086652   | 2030485 | 497476  | 2233094   |
| ABC                          | -   | 2170202 | 494641  | 2233072   |
| ABC                          | -   | 2170218 | 494657  | 2233117   |
| ABC                          | -   | 2030479 | 497460  | 2233088   |
| ABC                          | -   | -       | 2170189 | 2233139   |
| ABC                          | -   | 2170195 | 497448  | 2233050   |
| ABC                          | -   | -       | 494635  | -   |
| ABC                          | -   | -       | 2172343 | -   |
| ABC                          | -   | 2030463 | 497454  | 2233066   |
| ABC                          | -   | -       | 497426  | -   |
| D1 STANDARD MULTIPACKS (7 m) | 6 mm  | 9 mm    | 12 mm   | 19 mm   |
| ABC                          | -   | 1920480 | 1920481 | Contact your RS Components team for availability. |



## D1 Durable Vinyl Labels

Industrial strength adhesive helps to ensure labels stay stuck to a variety of surfaces.  
 Temperature rating: -40°C to 80°C

| D1 DURABLE LABELS (3 m)   | 12 mm   |
|---------------------------|---------|
| ABC                       | 1245866 |
| ABC                       | 1245865 |
| ABC                       | 1245867 |
| D1 DURABLE LABELS (5.5 m) | 12 mm   |
| ABC                       | 1245864 |



## D1 Permanent Polyester Labels

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins and more.  
 Temperature rating: -40°C to 150°C\*

| D1 PERMANENT POLYESTER (5.5 m) | 12 mm   | 19 mm   |
|--------------------------------|---------|---------|
| ABC                            | 4493945 | 4493939 |

\*depends on surface



## D1 Flexible Nylon Labels

Specifically designed for curved surfaces and wire and cable marking.  
 Temperature rating: -40°C to 60°C

| D1 FLEXIBLE NYLON (3.5 m) | 12 mm   | 19 mm   |
|---------------------------|---------|---------|
| ABC                       | 4493658 | 4493951 |



The DYMO® high quality labels are made in Belgium



This information is being provided for general information purposes and the compliance standards and certifications referenced herein are based on current standards which are subject to change.

